

NACRA 17 CLASS



The following amendments to the Class Rules have been approved to be effective 14 August 2013:

C.6. BOAT

C.6.1 MODIFICATIONS

Delete present rule and insert:

“(c) The Righting Line may be altered to a minimum diameter of 5 mm and a minimum length of 4500 mm, led under the trampoline with both ends fixed to the Front Cross Beam at either sides of the hulls and held under tension by the use of shockcord and rings. “

C.6.2 MAINTENANCE

(c)

Add new rule:

“(3) The four supplied blocks for the Gennaker sheets, maybe changed to any type of block with a minimum sheave diameter of 38mm and a maximum of 60mm.”

C.6.4 WEIGHT

Add :

The weight of the **boat** in dry condition shall be minimum 139.0 kg with the carbon fibre mast.

C.7.1 MODIFICATIONS

Insert new rule (d):

“(d) Two Nacra foot straps may be fitted to each **hull**, aft of the rear cross beam”

Renumber current (d) to (e) and current (e) and (f)

Insert new rule e (ii):

“(ii) to fit foot straps”

C.9 BEAMS

C.9.1 MODIFICATIONS

Add new rule:

“(e) A hook may be fitted to each end of the ‘chicken line’. (The line which exits either side of the aft cross beam.)”

NACRA 17 CLASS



Section H: MANUFACTURED PART LIST

Delete:

Qty	Component	Associated Hardware	Iden. sticker	Ident. Nr.	Options or tolerances
2		Gennaker sheet HK2636 40 mm			Or HK2137 ±2mm diam. sheave

Section I : RIGGING LIST

Amend line to read:

<i>Running Rigging</i>	<i>Size</i>			<i>Associated Hardware/material</i>	<i>Remark/tolerances</i>
	<i>Qty</i>	<i>length</i>	<i>diam.</i>		
Righting line	1	4500			As per C.6.1(c)